



Model	Capacity (#/hour)	Storage		Deaerator		Dimensions			Overflow	Steam Inlet	Weight - Lbs.		
		Cu. Ft.	Gallons	Diameter	Shell Length	A	B	C			Shipping	Operating	Flooded
5SS-L	5000	13	100	36"	5'-0"	8'-4"	4'-9"	4'-10"	1"	2-1/2"	2600	3500	4400
10SS-L	10000	26	200	36"	6'-8"	10'-0"	4'-9"	4'-10"	1"	3"	2950	4650	5700
15SS-L	15000	40	300	42"	6'-3"	9'-7"	5'-3"	5'-4"	2"	4"	3250	5800	6650
20SS-L	20000	53	400	42"	8'-7"	11'-11"	5'-3"	5'-4"	2"	5"	3900	7300	8250
30SS-L	30000	80	600	48"	8'-9"	12'-1"	5'-9"	5'-10"	2"	6"	4800	9850	10100
45SS-L	45000	120	900	54"	11'-1"	14'-5"	6'-3"	6'-4"	2"	8"	5700	13250	14850
60SS-L	60000	160	1200	54"	15'-0"	19'-0"	6'-3"	6'-4"	3"	8"	6900	16950	18600
75SS-L	75000	200	1500	60"	15'-0"	18'-4"	6'-9"	6'-10"	4"	10"	9050	21500	23750
90SS-L	90000	240	1800	60"	19'-0"	22'-4"	6'-9"	6'-10"	4"	10"	9100	24400	26550

NOTES:  
 - PIPING SHOWN AS DOTTED IS BY OTHERS  
 - 'X' STAND HEIGHT WILL VARY DEPENDING UPON PUMP  
 - DIMENSIONS & WEIGHTS ARE FOR REFERENCE ONLY

**LOCKWOOD PRODUCTS, INC.**  
 ATLANTA, GEORGIA

LOCKWOOD MODEL SS-L DEAERATOR  
 TYPICAL LAYOUT

DRAWN BY:	N.J.M.	DATE:	11/24/08
CHECKED BY:		REVISED:	
SCALE:	NONE	DWG. NO.:	SS STD